

RobustLink Central Manager

Centralized M2M Management Platform

for GoRugged R3000, M1000 XP and M1000 Pro V2

Robustel RobustLink is an industrial-grade centralized management and administration system for Robustel GoRugged R3000, M1000 XP and M1000 Pro V2. It allows you to monitor, configure and manage large numbers of remote devices on a private network over the web.

Key Features

- Remote Monitoring
- Remote Configuration
- Remote Firmware Upgrade
- Data Forwarding
- Number of Devices: 1000+
- Management: Web

Hardware Requirements

Your host hardware must meet the following minimum requirements:

- Pentium IV or above
- 1 GHz CPU (1.5 GHz recommended)
- 1 GB RAM (2 GB recommended)
- 1 GB disk space

Software Requirements

- O/S: Windows, Linux
- Apache 2.2, MySQL 5.5, PHP 5.4 or above
- Browser: IE 6.0 or above, Chrome, Firefox

The screenshot displays the RobustLink Central Manager web interface. At the top, the Robustel logo is on the left and the user name 'Robustel' is on the right. Below the logo is a navigation menu with 'HOME', 'CONFIGURATION', 'ADMINISTRATION', and 'HELP'. A 'Records per page' dropdown is set to '25', and a search box is present. The main content area features a table with columns: Index, Status, Device ID, Device Type, IMEI, RSSI, IP Address, Version, Region, Sync, and Details. The table contains four rows of data. The first row has a red 'X' status, while the others have green checkmarks. The 'Details' column for each row contains a 'Config' link. Below the table, a detailed view for the selected device (Device ID: 123456789012366) is shown, listing various attributes like Device Type, IMEI, IMSI, RSSI, Register, Operator, Cell ID, SMS Center, ToTal SIM Number, Current SIM Number, IP Address, DNS1, DNS2, Online Time, and Transmit State. At the bottom of the interface, it shows 'Records from 1 to 25 (Total: 31)' and navigation buttons for 'First', 'Prev', '1', '2', 'Next', and 'Last'. A copyright notice 'Copyright © 2013 Robustel Technologies. All rights reserved.' is at the very bottom.

Index	Status	Device ID	Device Type	IMEI	RSSI	IP Address	Version	Region	Sync	Details
1	✘	11234	M1000_ProV2		0					Config
2	✔	123456789012352	M1000_ProV2	310098562764001	28	172.16.2.1	2.0.0		⚠	Config
3	✔	123456789012359	M1000_ProV2	310098562764002	22	172.16.2.2	2.0.0		⚠	Config
4	✔	123456789012366	M1000_ProV2	310098562764003	23	172.16.2.3	2.0.0		⚠	Config

Device ID:	123456789012366
Device Type:	M1000_ProV2
IMEI:	310098562764003
IMSI:	567896843267003
RSSI:	23
Register:	Registered Home Network
Operator:	Mobile Company
Cell ID:	2B39,C903
SMS Center:	1380020003
ToTal SIM Number:	2
Current SIM Number:	SIM2
IP Address:	172.16.2.3
DNS1:	119.80.8.3
DNS2:	119.80.8.4
Online Time:	30
Transmit State:	0

Contact:

www.robustel.com

info@robustel.com